Premium Inclusions

PRE-CONSTRUCTION

- Soil report and Feature Survey
- Bushfire Attack Report
- Property Services Information
- 6 star Energy Report
- Building Permit
- Statutory Warranty Insurance
- 90 day maintenance
- One on One Colour Consultation

SITE WORKS & CONNECTIONS

- Earthworks based on a 5 metre setback on a maximum site of 650sqm with up to 300mm of fall over the land.
- Engineer designed "M" Waffle class slab:
 - 310mm overall height
 - 300mm wide perimeter beams
 - 3-L11 Trench mesh
 - 110 wide internal ribs with 1No. N12 bars
 - SL72 Top mesh
- Water connection to an existing dry tapping point within the building site.
- Connections to standard sewer and storm water points within the building site at a depth of up to 1.5m on a maximum site size of 650sqm.
- Single Phase underground electricity connection to an existing dedicated pit within 12m of the meter box and gas connection where available.
 (Note: Electricity, gas and telephone consumer account opening fees are excluded. Excludes rock removal, bushfire protection measures and

STRUCTURAL

telephone conduits).

Single Storey

- 2590mm ceiling height with 90mm Pine frame.
- 22.5° roof pitch to house and garage with Structural Pine roof trusses.

Double Storey

- 2590mm ceiling height with 90mm Pine frame to ground floor.
- 2440mm ceiling height with 90mm Pine frame to first floor.
- 22.5° roof pitch to house and garage with Pine roof trusses.

EXTERNAL

• Choice of Designer Facades (house specific) excluding feature finishes.

- Choice of clay wire cut bricks from Builders Category 1 Range with natural mortar and rolled joints.
- Selection of concrete roof tiles from Builders Category 1 Range.
- Colorbond fascia, gutter and downpipes from Builders Category 1 Range.
- Window Infills: Brickwork over steel lintel to openings up to 3000mm wide (lightweight infills over opening greater than 3000mm).
- Total of 2 garden taps:
 - 1 at meter location
 - 1 attached to dwelling

Double Storey

- Rendered lightweight cladding to first floor walls.
- Balcony (Double Storey only, Facade specific)
- Ceramic Floor Tiles selected from Builders Category 1 Range (up to 400 x 400mm).
- Feature aluminium balustrade or lightweight cladding (refer to working drawings)
- Minimum 450mm Eaves to entire first floor only. (facade specific)

EXTERNAL WINDOWS, DOORS & DOOR FURNITURE

- Designer aluminium powder-coated improved awning windows to front facade.
- Sliding windows to remainder of side and rear of dwelling.
- Designer aluminium powder-coated improved sliding door to Alfresco (house specific).
- Aluminium framed flyscreens with fibreglass mesh to all openable windows.
- Keyed window locks to all openable windows.
- Front Entry door: Feature 2040 x 820mm with clear glazing and painted finish.
- Entrance Lock: Terrace entrance knob lockset.
- External Laundry Door: 2040 x 820mm solid laminated timber 1 Lite with clear glazing and painted finish.
- External Garage Door: 2040 x 820mm Tempered hardboard flush panel (house specific).

- External Garage and Laundry Door Locks: Terrace entrance knob lockset.
- Garage Pedestrian Door: Flush panel 2040 x 820 with Terrace entrance knob lockset.
- Sectional Colorbond Garage Door: Choice of Colorbond colours from Builders standard range.
- Remote control with two hand held transmitters and one wall mount transmitter
- Painted timber beam over Garage Door opening to Single and Double Storey homes.

External Walls (house specific)

- Integrated Garages: Brick Veneer to Single and Double Storey homes.
- Detached Garages: (Double Storey homes) single skin brickwork with piers.

Alfresco (house specific)

 Undercover Alfresco area lined with painted plaster ceilings and concrete floor as part of slab (design specific).

ENERGY EFFICIENCY

- R2.5 Ceiling Batts to dwelling (excluding Garage, Porch and Alfresco ceilings)
- R1.5 Wall Batts to external house walls (including Garage/House common wall).
- Foil wrap to external walls including Garage (house common wall).
- Self-sealing exhaust fans to showers with draft stoppers.
- Rinnai solar hot water system with single roof panel and ground mounted 175 litre storage unit with natural gas booster.

Double Storey

 Rinnai solar hot water system with single roof panel and ground mounted 215 litre storage unit with natural gas booster.

CORNICE, SKIRTING, ARCHITRAVES, INTERNAL DOORS

- 75mm Cove Cornice to House and Garage.
- 67 x 18mm Square Edge MDF skirting boards with painted finish.
- 67 x 18mm Square Edge MDF architraves with painted finish.
- 2040mm high hinged flush panel doors with painted finish.

- 2040mm high hinged flush panel doors to all robes and linen cupboards with painted finish.
- Chrome hinges, latches and striker plates throughout home.

INTERNAL DOOR FURNITURE

- Designer 100 series leverset on round rosette to internal hinged passage doors.
- Chrome knob to robe and linen cupboards.

KITCHEN

- Designer Kitchen with 20mm reconstituted stone benchtop.
- Square edge laminated doors with choice from Builders Category 1 Range of colours.
- Fully modular cabinets with one bank of cutlery drawers and one bank of two pot drawers.
- Dishwasher provision with cold water connection and single power point.
- Pantry/Prep Room with 4 fixed white melamine shelves.
- Choice of Designer cabinetry handles from Builders Category 1 Range.
- Designer double bowl stainless steel sink with side drainer.
- Designer Kitchen chrome mixer tap

KITCHEN APPLIANCES

Choice of either packages:

- 900mm ILVE Stainless Steel underbench oven from Builders Category 1 Range,
- 900mm ILVE Gas Cooktop from Builders Category 1 Range,
- 900mm ILVE Undermount Extractor Rangehood from Builders Category 1 Range,
- 600mm ILVE Stainless Steel Dishwasher from Builders Category 1 Range.

OR

- 900mm ILVE Duel Fuel Upright Stainless Steel Cooker from Builders Category 1 Range,
- 900mm ILVE Stainless Steel Canopy Rangehood from Builders Category 1 Range.
- 600mm ILVE Stainless Steel Dishwasher from Builders Category 1 Range.

(NOTE: Single Storey Homes ducted to roof space and Double Storey Homes vented through the external wall).

LAUNDRY

- Stainless Steel trough with bypass set into custom built laminated cabinet.
- Chrome mixer tap with concealed washing machine stops.
- Linen cupboard with 4 rows of melamine shelving; Broom cupboard with single melamine shelf (house specific).

ENSUITE & BATHROOM

- Designer vitreous china basin with chrome waste outlet from Builders Category 1 Range.
- Designer laminated vanity unit with 20mm reconstituted stone benchtop.
- Polished edge mirrors to width of vanity.
- Designer semi framed 2000mm high shower screen with pivot door.
- Recessed tiled shower base with chrome waste outlet.
- Feature Designer acrylic bath.
- Designer closed couple vitreous china duel flush toilet suite with soft close seat.
- Designer chrome basin mixer tap from Builders Category 1 Range.
- Designer chrome shower rail and rose from Builders Category 1 Range.
- Designer chrome shower mixer tap from Builders Category 1 Range.
- Designer chrome bath mixer tap from Builders Category 1 Range.
- Designer chrome bath spout from Builders Category 1 Range

ELECTRICAL

- Double power points throughout home (excluding fridge, microwave, dishwasher, garage sectional door).
- LED Downlights (10w) throughout home, including Porch and Alfresco (excluding garage).
- External flood light to Laundry external door.
- 2 TV points with 5m of coaxial cable left in the ceiling for future antenna connection by client (if required).
- One pre-wired wall plated telephone

- point to Kitchen.
- Hardwired smoke detectors with battery backup.
- RCD safety switch and circuit breaker to meter box.

(NOTE: Refer to electrical drawing for indicative location of points).

HEATING

- Gas Ducted Heating Unit installed in roof space with digital thermostat hard wired to wall, ducted to living areas and bedrooms throughout (excludes wet areas).
- Total number of points and unit size are determined by supplier for maximum efficiency.

FLOOR AND WALL COVERINGS

Floor Coverings

- Ceramic Floor Tiles or 8mm Laminate (Selection from Builders Category 1 Range) to Entry, Living, Meals and Kitchen.
- Ceramic Floor Tiles to Ensuite, Laundry, WC and Bathroom. Selection from Builders Category 1 Range (up to 400 x 400mm). Design specific.
- Tiled skirting: To wet areas (up to 100mm).
- Carpet: To all remaining areas including Rear Hallway. Selection from Builders Category 1 Range.

Wall Tiles

 Ceramic Wall Tiles: To Kitchen, Bathroom, Ensuite and Laundry.
 Selection from Builders Category 1 Range (up to 400 x 400mm).

PAINT

- Taubmans 2 Coat Flat Acrylic Paint System paint to all internal walls.
- Taubmans 2 Coat Flat Acrylic Paint System paint to ceilings.
- Taubmans Gloss Enamel Paint to all interior skirting, architraves and doors.
- Taubmans Exterior to all exterior painted surfaces.

Stairs (Double Storey only)

- MDF staircase with painted handrail
- Newel post and timber balusters (design specific)

| lient Signature (1) | Client Signature (2) | Sales Consultant Signature |
|---------------------|----------------------|----------------------------|
| ite Address | | Date |

